

ISOGUARD-WP

ACRYLIC POLYMER BASED WATERPROOF COATING



DESCRIPTION:

Isoguard-WP is a pure acrylic polymer based liquid specially designed for making polymer modified cementitious based waterproof coatings. It is the most cost effective polymeric waterproofing solution.

ADVANTAGES:

- ✓ Easy to use product which needs to be mixed with cement
- ✓ Prevents carbonation
- ✓ Possesses high compressive strength
- ✓ 100% waterproofing solution

AREAS OF APPLICATION:

Isoguard-WP is mainly recommended for waterproofing of terraces, toilets, bathrooms, sunken slabs, basements and also water tanks. It can be used on floor or external walls. It can be used on sunken portion of bathrooms, toilets, balconies etc. Also it can be used as an additive for cement paints, white and grey cement to improve water resistance and bonding properties, preventing chalking.

SPECIFICATIONS:

| | |
|-----------------------------------|----------------------|
| Base | Acrylic |
| Colour | White |
| Water Permeability (two coats) | NIL |
| Coverage | 55-60 sq.ft./kg/coat |
| Pot Life after mixing with cement | 30 mins (approx.) |

PREPARATION:

Preparation of surface for any waterproofing work is extremely important. Fill all cracks with Fix 'N' Bond, clean surface of dirt, dust and all loose particles. Cure the repaired cracks. Scrub and clean the surface. Wet the surface 24 hours prior to coating Isoguard-WP.

METHOD OF APPLICATION:

Pour 1 litre of Isoguard-WP into 1.25 kgs of cement slowly. Stir it with rod and mix thoroughly till the mixture is lump free. Apply the mixture to the desired surface within 30 mins of mixing by brush. Apply the second coat after 24 hours. Let the surface now cure for 7 days.

SAFETY PRECAUTIONS:

Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

PACKING:

Available in 20 & 200 Litres.

WARRANTY CLAUSE: *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*

