

BITUFILL

RUBBERISED JOINT FILLER COMPOUND



DESCRIPTION:

Bitufill is a rubberized joint filler compound which is formulated as such that it can be cold poured directly from the container into crack fractures in asphalt surfaces for the purpose of sealing cracks, thus avoiding future maintenance resulting from untreated and exposed cracks.

ADVANTAGES:

- ✓ Single component paste, cold poured, thus ready to use.
- ✓ Excellent adhesion to concrete, bricks, precast blocks, wood and metal
- ✓ Can be used where joint movement is +/- 5%.
- ✓ Excellent elasticity in wide temperature variations
- ✓ Minimum shrinkage
- ✓ 100% Waterproof
- ✓ Can be applied on vertical as well as horizontal surfaces because of its non-sagging properties

AREAS OF APPLICATION:

Bitufill is used to filling cracks of CI/Cement drainage pipes, AC/GI sheets, gutters, joints, cracks of upto 5mm. in masonry surfaces, terraces, basements, concrete precast blocks, slabs, brick linings, water tanks, irrigation canals etc.

SPECIFICATIONS

Base	Bitumen
Colour	Black
Appearance	Semi-Viscous Liquid
System	Single Component
Finish	Smooth & Semi-Glossy
Drying Time:	
Surface Dry	3-4 Hours
Hard Dry	24 Hours
Recommended Coats	1-2
Coverage	Depends on width & Depth of Cracks
Resistance to Heat	80-90° C.
Flash Point	Above 40° C.

PREPARATION:

Clean the joints, cracks, gaps so as to make it free from dust, loose particles, oil grease etc. For better results, apply one coat of **TRANSPROOF** as bonding agent on the areas to be treated.

METHOD OF APPLICATION:

Fill the joints, cracks gaps by spatula, putty knife or finger. Avoid formation of cavity or bubbles. Leave the treatment to dry for at least 24 hours. Inspect the treatment after 24 hours. If shrinkage is observed, then top up the joint, crack, gap, etc. to the level of surface, and let it dry as suggested.

CLEANING OF TOOLS:

Clean the tools and hands with kerosene or mineral turpentine.

PACKING:

Available in 4 & 20 Litres

SAFETY PRECAUTIONS

Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

WARRANTY CLAUSE: *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*