

NODROPS-ACC

ANTI CONDENSATION COATING

DESCRIPTION:

NODROPS-ACC is a high quality anti-condensation coating recommended for use on areas where there is sudden temperature variations. It is suitable on ceilings, underside of roof sheets, ducting, internal walls, steel building frames, pipe work etc. NODROPS-ACC inhibits condensation by absorbing moisture and improving insulation. It contains a biocide for the sole purpose of protecting the paint.

ADVANTAGES:

- ✓ Single component, ready to use coating
- ✓ Prevents condensation on surfaces, thus protecting paint
- ✓ Excellent ageing properties
- ✓ Is extremely effective where there is a sudden variation in temperature

AREA OF APPLICATION:

It is highly recommended for use in rooms where there is sudden variation in temperature such as air conditioned rooms, highly humid areas, cold storages, AC plants, kitchens, bathrooms, basements, steam rooms etc.

SPECIFICATION:

Base	Acrylic
Colour	White
Appearance	Semi-Viscous Liquid
System	Single Component
Finish	Smooth & Semi-Glossy
Drying Time:	
Surface Dry	1-2 Hours
Hard Dry	6-8 Hours
Film Property	Flexible
Recommended Coats	2
Coverage	55-60 sq.ft./litre/coat on smooth surface
Resistance to Heat	Upto 100° C.
Cold Resistance	Sub Zero Temp.
Flash Point	Above 30° C.

PREPARATION:

Do not coat on freshly plastered walls (only after 28 days of curing). In order to obtain maximum adhesion, the surface must be clean free of loose dirt, grease, algae, fungus etc. Clean and thoroughly wash with fungicide solution prior to coating. For chalky surfaces, a prime coat of **ACRYPRIME-20** is recommended prior to coating **NODROPS-ACC**. Also a primer is recommended in areas which cannot be prepared as above and which are already coated with conventional paints.

METHOD OF APPLICATION:

Can be applied with brush/roller/Spray. Minimum two coats are recommended. For better finish use fur type roller.

CLEANING OF TOOLS:

All tools and equipments should be washed with mineral turpentine.

SAFETY PRECAUTIONS:

Keep away from naked flames/lights. Do not smoke near application area. Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

PACKING:

Available in 4 & 20 Litres.

WARRANTY CLAUSE: *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*