

TACKPLAST

BONDING ADDITIVE FOR PLASTER

DESCRIPTION:

TACKPLAST is a specially formulated bonding agent for plasters which, when added in the recommended dosage in cement, increases the bonding strength between plaster and old concrete.

ADVANTAGES:

- ✓ Provides excellent bonding to various surfaces
- ✓ Prevents wastage of plaster, thus saving cost of cement drastically
- ✓ Bond strength increases as concrete cures
- ✓ Resistant to alkalis, sulphates and chlorides
- ✓ Does not affect reinforcement
- ✓ Enhances adhesion to steel surfaces

AREAS OF APPLICATION:

TACKPLAST is used on horizontal and vertical surfaces both. It is useful in enhancing the adhesion cement to surfaces against gravity, for example, ceilings, where the chance of wastage of plaster is more. It is also used for repair work in tall buildings.

SPECIFICATIONS:

COLOUR	MILKY WHITE
RECOMMENDED DOSAGE	3-4% OF WEIGHT OF CEMENT

PREPARATION:

Make sure that the surfaces is clean of dirt, dust, oil, grease etc, as this is one of the major factor which can affect the product application.

METHOD OF APPLICATION:

Mix the product in the above recommended dosage and mix thoroughly. Add only 3-4 % of the product of the weight of cement and rest water according to desired viscosity. Do not overdose.

CLEANING OF TOOLS:

Clean tools with water.

SAFETY PRECAUTIONS:

Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

PACKING:

Available in 20, 50 & 100 Litres.

***WARRANTY CLAUSE:** The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*

