

EP-REDOX-415

EPOXY REDOXIDE PRIMER

DESCRIPTION:

EP-REDOX-415 is a two-component, red oxide epoxy primer. EP-REDOX-415 has excellent adhesion to steel and other metal surfaces.

ADVANTAGES:

- ✓ Good adhesion and flexibility to the surfaces applied.
- ✓ It has good corrosion resistance in chemical environment.
- ✓ It is a metal primer used in pulp, paper mills, refineries, petrochemicals and metal and engineering industries.

AREAS OF APPLICATION:

Used as a base coat/primer, prior to Epoxy Top Coats.

SPECIFICATIONS:

Base	Epoxy
Colour	Red
System	Two Component (Resin: Hardener, 85:15 by volume)
Finish	Smooth and Matt
Drying Time:	
Surface Dry	1-2 Hours
Hard Dry	6-8 Hours
Recommended Coats	1
Coverage	90-100 sq.ft./litre/coat
Resistance to Heat	Upto 100° C to 120° C.
Flash Point	Above 30° C.
Scratch Hardness	Excellent

SAFETY PRECAUTIONS:

Avoid inhalation of solvent vapour or paint mist and contact of contents of liquid paint with skin and eyes. Provide face ventilation when working with solvent borne coatings in confined spaces or stagnant air. Provide respiratory, skin and eye protection. Do not smoke in the area and away from open flames, lights etc.

PACKING:

Available in 4 & 20 Litres.

STORAGE :

Store in a cool, dry place away from direct sunlight.

WARRANTY CLAUSE: *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied, shall be limited to only replacement of material.*

