

BITUSEALER

BONDING COAT FOR BITUMINOUS COATINGS

DESCRIPTION:

Bitusealer is a cold applied bituminous bonding coat which is used to bond bitumen based waterproof coatings. It is designed such that it seals porous surfaces and encourages the adhesion of bituminous waterproof coatings.

ADVANTAGES

- ✓ Easy to use, single component cold applied coating
- ✓ Sealer porous surfaces
- ✓ Excellent adhesion to almost all surfaces
- ✓ Excellent area coverage

AREAS OF APPLICATION:

Bitusealer is primarily used on surfaces such as concrete floors, asbestos sheets, Concrete Asbestos cement, lightweight concrete screeds, metal surfaces etc where bonding of Bitucoat and

SPECIFICATIONS:

Appearance	Black liquid
Base	Bitumen
Coverage:	
Metal	80-85 sq.ft./litre/coat
Concrete	60-70 sq.ft./litre/coat
Flash Point	Above 30°C
Drying Time:	
Surface Dry	30 minutes
Hard Dry	1 ½ -2 Hours

PREPARATION:

Make sure surface is free from oil, grease, dirt, dust and loose debris. On metal surfaces all loose rust should be removed using a wire bristled brush and where advanced signs of corrosion are evident these areas should initially be treated with Conrust. Surfaces should preferably be dry although Bitusealer will adhere to damp but not wet surfaces.

METHOD OF APPLICATION:

Can be sprayed or applied by brush/roller.

CLEANING OF TOOLS:

Clean hands tools with water immediately, any hardened material in the area can be removed by spatula, scrapper, etc.

SAFETY PRECAUTIONS:

Keep away from naked flames/lights. Do not smoke near application area. Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

PACKING:

Available in 4 & 20 Litres.

WARRANTY CLAUSE: *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*

the complete construction solution