

ACROSEAL

ACRYLIC RUBBER BLEND SEALANT

DESCRIPTION:

ACROSEAL sealant is a solvent based sealant, which is a blend of acrylic and rubber. It is best suited for cracks and joints, indoor and outdoor, which require certain amount of elasticity.

ADVANTAGES:

- ✓ Excellent adhesion to all common construction materials
- ✓ Can withstand extreme temperature variations
- ✓ Tough yet flexible. Can accommodate normal contraction and expansion of structures
- ✓ Single component white paste.
- ✓ Self curing and no primer required.
- ✓ Can be applied for joints with more than 15mm of depth/width
- ✓ Paintable
- ✓ Does not crack, shrink, peel or sag

AREAS OF APPLICATION:

ACROSEAL can be used for filling cracks in concrete surfaces, concrete blocks, slabs, brick lining. It is also used for corrugated roofs, asbestos, cement sheets, valley gutters, 'J' bolts. In the roofs G.I./ C.I. pipe joints etc. For stopping leaks from Joints around bathtubs, wash basins, kitchen platform, sinks etc. It also has various industrial application in the field of Automobile applications like headlight reflectors, windshields fixing, sealing joints in bodies, sound insulation etc. It can find various uses in the appliance industry for sealing various types of joints etc. Prefabricated homes, Mobile homes etc. In irrigation canals, aqueducts, pre-fabricated irrigation channel blocks, etc.

SPECIFICATIONS:

Base	Acrylic & Rubber
Appearance	Thick Paste
Colour	Off White
Skin Forming	15-20 mins @ 30
Volume Shrinkage	<15%
Elongation	>150%
Temp Resistance	-5° C to 110° C
Coverage	Depending on depth and width of cracks

PREPARATION:

Clean the joints/cracks/gaps from dirt, dust, oil, grease, loose particles and old sealant if any. Care should be taken to remove any alkaline deposits from cement or concrete by using ammonia solution/water. Glass, aluminium or glazed surfaces should be cleaned with mineral spirits.

APPLICATION:

Fill the joints/cracks/gaps with sealant by using spatula, putty knife or fingers. Avoid formation of cavity or bubbles during application. Level the surface with wet knife/spatula. Any tooling should be done prior to skin formation.

CLEANING OF TOOLS:

Clean tools and hands with soap water.

SAFETY PRECAUTIONS:

Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

PACKING:

Available in 5 & 25 Kgs.

WARRANTY CLAUSE: The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.