

## **PRIMER W-30**

### ***WATER BASED PRIMER***

#### **DESCRIPTION:**

PRIMER W-30 is single component, specially formulated primer which acts as a primer as well as a binder over plastered and painted surfaces. It is designed specifically for ENDODAMP-414 and DÉCOR-PROOFER.

#### **ADVANTAGES:**

- ✓ No skilled labour required.
- ✓ Easy to use single component.
- ✓ Can be applied with a brush, spray or roller.
- ✓ Excellent as base coat primer over plastered surfaces.
- ✓ Seals all pores on the surface and reduces the porosity of the surface.
- ✓ Increases the coverage of **DÉCOR PROOFER** by 20% to 30%. Especially recommended for use as primer before **ENDODAMP-414** and **DÉCOR PROOFER**.
- ✓ Putty can be made with White Cement/Plaster of Paris etc. for filling cracks of internal walls of plaster before lime work.
- ✓ Does not crack, spall, peel or disintegrate excellent flexibility.

#### **AREA OF APPLICATIONS :**

Primer-W30 can be applied to surfaces such as parapets, chajjas, external wall of buildings etc. and as primer coat for **ENDODAMP-414** and other paints, distempers. Also, it is applied over lime Plasters and as primer before cement based paints.

#### **SPECIFICATIONS:**

Colour	White
Viscosity	40-100 cps
Solids	30 +/- 2 %
Coverage	60-70 sq.ft./litre/coat

**PREPARATION:**

Fill all visible cracks, joints etc with CRACK 'O' FILL. Allow to dry for 24 hours or leave overnight. Apply one coat of **PRIMER W-30** over the plastered surface or the surface wherever treatment is to be carried out as stated above. Allow to dry for 6 -8 hours. Now the surface is ready for further treatment.

**METHOD OF APPLICATION:**

Stir the contents thoroughly. Apply one coat of **PRIMER W-30** over prepared surface. Allow to dry for 6-8 hours before applying over coat

**CLEANING OF TOOLS:**

Clean hands and tools with water.

**STORAGE:**

Store in a cool, dry place, away from direct sunlight.

**PACKING :**

Available in 4 & 20 litres.

***WARRANTY CLAUSE:** The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material*

the complete construction solution