

TOPFIX-2K

RAPID SETTING REPAIR MATERIAL

DESCRIPTION:

TOPFIX-2K, is a three component, high build repair material, mainly for repair work of concrete, bitumen or any other horizontal surface. It is used where rapid setting and minimum traffic interruption is required. It is most suitable for repairs of concrete, kota, trimix and bitumen surfaces in roads, airfields and factories.

ADVANTAGES:

- ✓ Prepacked components
- ✓ Rapid setting in 30 mins to 60 mins
- ✓ More than 60MPA strength in 1 day
- ✓ High strength, abrasion and weather resistant
- ✓ Hand or mechanical mixing
- ✓ Greatly reduces thermal load on surfaces
- ✓ Self-leveling/compacting and does not require vibration

AREAS OF APPLICATION:

TOPFIX-2K is mainly used in concrete and bitumen roads, trimix surfaces and kota stone potholes.

SPECIFICATIONS:

Colour	Concrete Grey/ Black
Appearance	Viscous Liquid
System	3 Component
Finish	Smooth & Matt
Drying Time:	
Surface Dry	1/2 hour
Hard Dry	1-4 hours
Recommended Coats	2
Compressive Strength	1 Hour: > 25 MPA 1 Day: > 60 MPA 3 Days: > 80 MPA

PREPARATION:

Clean all foreign matter such as dirt, dust, grease, laitance, mortar droppings, loose and flaking materials. Moss and fungus must be removed using suitable fungicide solution or bleach or dilute HCL solution, thereafter wash thoroughly. Necessary repairs to defects must be carried out prior to coating like crazed unstable or hollow surfaces, major cracks, any protrusion, outlets, construction joints etc.

METHOD OF APPLICATION:

Mixing can be carried out manually or by machine. Mix all 3 components thoroughly till homogenous mixture is achieved. Pour the material in the desired area and clean off excessive material immediately.

CLEANING OF TOOLS:

Clean the tools, brush immediately with water.

SAFETY PRECAUTIONS:

Keep away from naked flames/lights. Do not smoke near application area. Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

PACKING:

Available in 5 & 25 kgs.

WARRANTY CLAUSE: *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*

