

## **ACEFIX-555**

### ***NON SHRINK, READY TO USE REPAIR MORTAR***

#### **DESCRIPTION:**

ACEFIX-555 is general purpose, non-shrink, and ready to use wet mix mortar. It is a single component product and self-curing. It does not need any pre or post water addition, thus saving water cost.

#### **ADVANTAGES:**

- ✓ High bonding strength
- ✓ Does not crack or shrink
- ✓ Ready to use, hence consistent controlled quality
- ✓ Non Metallic and Chloride free
- ✓ High early compressive strength
- ✓ Minimum downtime
- ✓ Waterproof
- ✓ UV resistant
- ✓ Self-curing

#### **AREAS OF APPLICATION:**

Ready to use and can be applied in tie rod holes, wall tile patty holes, for honeycombing, hairline , filling holes of scaffolding supports, framework ties etc.

#### **SPECIFICATIONS:**

Base	Mortar
Appearance	Grey paste
Pot life @ 30°C.	6-8 hours in shade
Compressive Strength 28 days	<b>Pourable</b> >10N/mm <sup>2</sup>
Coverage	As per usage at site
Compliance	Meets ASTM C1107 for Grade C type grouts.

**PREPARATION:**

Surface should be clean of dust, loose particles, grease, oil and foreign deposits should be removed from all surfaces with which the grout will come in contact.

**METHOD OF APPLICATION:**

Remove material from packing. Use as much as required and leave to air-dry until completely dry.

**CLEANING OF TOOLS:**

Clean all tools and equipment immediately after use with water. Once hardened, material can only be removed manually or mechanically.

**SAFETY PRECAUTIONS:**

Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details.

**PACKING:**

Available in 25 Kgs.

**WARRANTY CLAUSE:** *The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.*