

CRP-70

CHLORINATED RUBBER PAINT

DESCRIPTION:

CRP-70 is flexible, hard wearing chlorinated rubber paint, with good resistance to water in both acid and alkaline conditions.

ADVANTAGES:

- ✓ Resistant sea and fresh water (Not recommended for Potable Water systems for drinking water)
- ✓ Resistant to dilute acids and alkalis and mineral oils.
- ✓ Resistant to severe atmospheric pollution, e.g. Gas Plants and Sewage Installations.
- ✓ Resistance to spread of flame.
- ✓ Resistance to fungal growth.

AREAS OF APPLICATION:

CRP-70 is particularly suitable in conditions where conventional paints may fail. For example, it is used in dairy parlours, Silage Pits and Sewage Installations. It can also be used as a Swimming Pool Paint on properly treated surfaces.

SPECIFICATIONS:

Colour	White and Other selected shades
Drying Time	
Surface Dry	1 Hour
Hard Dry	3-4 Hours
Coverage	90-100 sq.ft./litre/coat on smooth surface
Flash Point	Over 25°C.
Application	Brush, Roller or Airless Spray.

PREPARATION:

Clean the surfaces free from loose and flaking materials, dirt, grease, wax etc. Sound paint should be tested for solvent reaction by applying CRP-70 over a small test area and checking for softening or lifting of the old film. Allow 24 hours between coats. If CRP-70 is used as a swimming pool coating on tiles, the surface must be properly roughened prior to use.

METHOD OF APPLICATION:

Brush Application:

No thinning is required.

Thinning ratio - up to 400gms of Thinner per 4 litres paint.

Airless Spray Application:

Thinning ratio up to 400gms of Thinner per 4 litres paint.

Spray tip aperture: 0.33 mm - 0.38 mm (13-15 thou)

Minimum working pressure: 2000 psi.

CLEANING OF TOOLS:

All tools, equipments, hands can be cleaned with solvents like Xylene, Toluene etc.

SAFETY PRECAUTIONS:

Keep away from naked flames/lights. Do not smoke near application area. Protective gear such as gloves and goggles should be worn when handling the product. Treat any splashes to the skin or eyes with fresh water immediately. Should the product be accidentally swallowed, do not encourage vomiting, but call for immediate medical assistance. Ensure that the container is available for medical attendant to examine any relevant instructions and content details

PACKING:

Available in 4 & 20 Litres.

WARRANTY CLAUSE: The product incorporated and sold is without Warranty expressed or implied, including warranty of Merchantability and fitness for use of this material and upon condition that purchaser shall make the own test to determine the suitability and quality of such products for their particular purpose. The user assumes all risks of use and handling, whether or not in accordance with any statement of the supplier. Supplier's liability if any, for any action arising out of the material being supplied shall be limited to only replacement of material.